



Reference Document	Document No.	LINDEN-SPE-7172
Title	Cable Spec – Buoyant Copper (-136)	

Cable Specification

Item No.	Component	Details
1	Cable OD	10.7 mm (0.420")
2	Cable OD Tolerance	±0.3mm (0.01")
3	Fiber	N/A
4	Jacket	Linden Proprietary Design; Aramid Braid/Foamed TPU
5	Attenuation @ 1310 nm (dB/km)	N/A
6	Attenuation @ 1550 nm (dB/km)	N/A
7	Optical Propagation Loss Measurements	N/A
8	Number of Conductors	Ten (10)
9	Conductor Gauge	4 x 20 AWG; 1 x 24 AWG Twisted Pair; 2 x 28 AWG Twisted Pair
10	Voltage Rating	600V (300V for 28 AWG TP)
11	Tensile Strength (lbs)	200
12	Safe Working Load (SWL)	Recommended guideline - 15% (30 lbs); SWL is application and environment dependent
13	Minimum Bend Radius (MBR)	Recommended guideline - 214 mm (8.40"); MBR is application and environment dependent
14	Serialization	All cables will have Cable ID number for traceability
15	Test Data	A package detailing optical propagation will be supplied with each shipment

OD (P/N): 10.7 mm (10-CU-O-260-FQ-420)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)