



Reference Document	Document No.	LINDEN-SPE-7184
Title	Cable Spec – Buoyant Copper (-149)	

Cable Specification

Item No.	Component	Details
1	Cable OD	14.4 mm (0.566")
2	Cable OD Tolerance	±0.3mm (0.01")
3	Fiber	N/A
4	Jacket	Linden Proprietary Design; Aramid/Foamed TPU
5	Attenuation @ 1310 nm (dB/km)	N/A
6	Attenuation @ 1550 nm (dB/km)	N/A
7	Optical Propagation Loss Measurements	N/A
8	Number of Conductors	Twenty One (21)
9	Conductor Gauge	20 x 26 AWG + Cat6
11	Tensile Strength (lbs)	200
12	Safe Working Load (SWL)	Recommended guideline - 15% (30 lbs); SWL is application and environment dependent
13	Minimum Bend Radius (MBR)	Recommended guideline - 288 mm (11.32"); MBR is application and environment dependent
14	Serialization	All cables will have Cable ID number for traceability
15	Test Data	A package detailing optical propagation will be supplied with each shipment

OD (P/N): 14.4 mm (20-CU-CAT6-O-336-FQ-566)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)