



Reference Document	Document No.	LINDEN-SPE-7224
Title	Cable Spec – Buoyant Copper (-181)	

Cable Specification

Item No.	Component	Details
1	Cable OD	5.3 mm (0.210")
2	Cable OD Tolerance	±0.3mm (0.01")
3	Fiber	N/A
4	Jacket	Linden Proprietary Design; Aramid Braid/Foamed TPU
5	Attenuation @ 1310 nm (dB/km)	N/A
6	Attenuation @ 1550 nm (dB/km)	N/A
7	Optical Propagation Loss Measurements	N/A
8	Number of Conductors	Two (2)
9	Conductor Gauge	2 x #24 AWG Shielded Twisted Pair; 1 x #26 AWG Drain Wire
10	Voltage Rating	300V
11	Tensile Strength (lbs)	400
12	Safe Working Load (SWL)	Recommended guideline - 15% (60 lbs); SWL is application and environment dependent
13	Minimum Bend Radius (MBR)	Recommended guideline - 106 mm (4.20"); MBR is application and environment dependent
14	Specific Gravity	1.025
15	Weight in Air	22.9 kg/km
16	Weight in Seawater (1.03 g/cm ³)	-0.11 kg/km
17	Serialization	All cables will have Cable ID number for traceability
18	Test Data	A package detailing optical propagation will be supplied with each shipment

OD (P/N): 5.3 mm (2-CU-O-110-FQ-210-YEL)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)

One Park Drive, Suite 10, Westford, MA 01886 978-392-7985; info@LindenPhotonics.com

www.LindenPhotonics.com

3 Feb 2020