



Reference Document	Document No.	LINDEN-SPE-7428
Title	Cable Spec – Copper (-389)	

## Cable Specification

Item No.	Component	Details
1	Cable OD nom.	7.6 mm (0.300")
2	Fiber	None
3	Jacket	Linden Proprietary Design; PVC/Aramid Braid/TPU
4	Attenuation @ 1310 nm (dB/km)	N/A
5	Attenuation @ 1550 nm (dB/km)	N/A
6	Optical Propagation Loss Measurements	N/A
7	Number of Conductors	Two (2)
8	Conductor Gauge	Two (2) x #14 19/27
9	Tensile Strength (lbs)	250
10	Safe Working Load (SWL)	Recommended guideline - 15% (38lbs); SWL is application and environment dependent
11	Minimum Bend Radius (MBR)	Recommended guideline – 152 mm (6"); MBR is application and environment dependent
12	Weight in Air (g/m)	82
13	Serialization	All cables will have Cable ID number for traceability

OD (P/N): 7.6 mm (2-CU-AA-O-242-Q-300)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)