



Reference Document	Document No.	LINDEN-SPE-7228
Title	Cable Spec – Hybrid (-187)	

## Cable Specification

Item No.	Component	Details
1	Cable OD	14.9 mm (0.85")
2	Cable OD Tolerance	±0.75mm (0.03")
3	Fiber	2 x Singlemode STFOC (LINDEN-SPE-7196)
4	Jacket	Linden Proprietary Design; Primary strength coating: STFOC/Aluminum-Polyester Tape Wrap/TPU/Aramid Braid/TPE
5	Attenuation @ 1310 nm (dB/km)	< 0.5
6	Attenuation @ 1550 nm (dB/km)	< 0.5
7	Optical Propagation Loss Measurements	Performed 100% on all cables at 1310nm and 1550nm
8	Number of Conductors	Two (2)
9	Conductor Gauge	16 AWG
10	Calculated SG	1
11	Tensile Strength (lbs)	2,200
12	Safe Working Load (SWL)	Recommended guideline - 15% (330 lbs); SWL is application and environment dependent
13	Minimum Bend Radius (MBR)	Recommended guideline - 298 mm (17"); MBR is application and environment dependent
14	Serialization	All cables will have Cable ID number for traceability
15	Test Data	A package detailing optical propagation will be supplied with each shipment

OD (P/N): 14.1mm (2-FO-2-CU-365-FQ-585-YEL)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)