



Reference Document	Document No.	LINDEN-SPE-7363
Title	Cable Spec – Hybrid (-331)	

Cable Specification

Item No.	Component	Details
1	Cable OD	11.7 mm (0.460")
2	Cable OD Tolerance	±0.58mm (0.023")
3	Fiber	4 x Singlemode in a Gel-Filled Polyamide 2.6 mm OD Tube
4	Jacket	Linden Proprietary Design; Primary strength coating: Aramid Braid/HDPE
5	Attenuation @ 1310 nm (dB/km)	< 0.5
6	Attenuation @ 1550 nm (dB/km)	< 0.5
7	Optical Propagation Loss Measurements	Performed 100% on all cables at 1310nm and 1550nm
8	Number of Conductors	Four (4)
9	Conductor Gauge	2 @ 18 AWG; 2 @ 24 AWG (drain wires); 1 @ 24 AWG (Sense wire)
10	Calculated SG	1.16
11	Tensile Strength (lbs)	3,200
12	Safe Working Load (SWL)	Recommended guideline - 15% (480 lbs); SWL is application and environment dependent
13	Minimum Bend Radius (MBR)	Recommended guideline - 238mm (9.4"); MBR is application and environment dependent
14	Serialization	All cables will have Cable ID number for traceability
15	Test Data	A package detailing optical propagation will be supplied with each shipment

OD (P/N): 11.7mm (4-FO-4-CU-O-55-S-65-S-460)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)