



Reference Document	Document No.	LINDEN-SPE-7469
Title	Cable Spec – Hybrid (-432)	

Cable Specification

Item No.	Component	Details
1	Cable OD nom.	10.9 mm (0.430")
2	Fiber	1 x LINDEN-SPE-7265; 2-channel singlemode GFLT
3	Jacket	Linden Proprietary Design; Polypropylene/Aramid Braid/TPU/HDPE
4	Attenuation @ 1310 nm (dB/km)	0.6
5	Attenuation @ 1550 nm (dB/km)	0.6
6	Optical Propagation Loss Measurements	Performed 100% on all cables at 1310nm and 1550nm
7	Number of Conductors	Two (2) x #16 AWG & one (1) x #18 AWG ground wire
8	Conductor Gauge	#16 AWG / #18 AWG
9	Tensile Strength (lbs)	1,000
10	Safe Working Load (SWL)	Recommended guideline - 15% (150 lbs); SWL is application and environment dependent
11	Minimum Bend Radius (MBR)	Recommended guideline - 218 mm (8.6"); MBR is application and environment dependent
12	Weight in Air (g/m)	95
13	S.G.	1.01
14	Operating Temperature (°C)	-40 to 90
15	Serialization	All cables will have Cable ID number for traceability

OD (P/N): 10.9 mm (4-FO-3-CU-O-388-FQ-400-S-430)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)