



Reference Document	Document No.	LINDEN-SPE-7310
Title	Cable Spec – High Temp STFOC (MM) 0.030”	

Cable Specification

Item No.	Component	Details
1	Cable OD	0.762 mm (0.030”)
2	Cable OD Tolerance	±0.13mm (±0.005”)
3	Fiber	Corning ClearCurve MM HTA (50/125)
4	Jacket	Linden Proprietary Design; Primary strength coating: LCP/FEP
5	Attenuation @ 850 nm (dB/km)*	3.5
6	Attenuation @ 1300 nm (dB/km)*	3.0
7	Optical Propagation Loss Measurements	Performed 100% on all cables at 1310nm and 1550nm
8	Tensile Strength (lb); measured at stress rate ~ 100 lbs/min	40
9	Tensile Strength measurement	Performed 100% on all cables at stress rate ~ 100 lbs/min; average of 5 samples, 1 m samples cut from end of finished cable
10	Serialization	All cables will have Cable ID number for traceability
11	Test Data	A package detailing optical propagation, loss and tensile strength data will be supplied with each shipment
12	Weight	0.75 kg/km nominal

OD (P/N): 762µm (1-W-A-24-J-30)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)

*Preliminary