



Reference Document	Document No.	LINDEN-SPE-7429
Title	Cable Spec – High Strength (-390)	

Cable Specification

Item No.	Component	Details
1	Cable OD	6.0 mm (0.236”) nom.
2	Fiber	Singlemode
3	Jacket	Linden Proprietary Design; GFLT/Aramid Braid/TPU
4	Attenuation @ 1310 nm (dB/km)	< 0.45
5	Attenuation @ 1550 nm (dB/km)	< 0.35
6	Optical Propagation Loss Measurements	Performed 100% on all cables at 1310nm and 1550nm
7	Tensile Strength (lbs)	450 lbs
8	Safe Working Load (SWL)	Recommended guideline - 15% (68 lbs); SWL is application and environment dependent
9	Minimum Bend Radius (MBR)	Recommended guideline -120 mm (4.7”); MBR is application and environment dependent
10	Weight in Air	31 g/m (21 lbs/1,000ft)
11	Specific Gravity	1.08
12	Serialization	All cables will have Cable ID number for traceability
13	Test Data	A package detailing optical propagation will be supplied with each shipment

OD (P/N): 6.0mm (1-SM-V-102-O-115-Q-236)

For color designation add the following to Cable P/N: Blue (-BLU); Brown (-BRN); Green (-GRN); Gray (-GRA); Orange (-ORN); Red (-RED); Violet (-VIO); White (-WHT); Yellow (-YEL); Black (-BLK)